

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
22 January 2004 (22.01.2004)


PCT

(10) International Publication Number
WO 2004/007777 A2

- (51) International Patent Classification⁷: C21C 5/56, (74) Agent: HERMAN DE GROOT, Johan, Willem; Corus Technology BV, P.O. Box 1000, NL-1970 CA IJmuiden (NL).
- (21) International Application Number: PCT/EP2003/007527
- (22) International Filing Date: 10 July 2003 (10.07.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
02077780.1 10 July 2002 (10.07.2002) EP
02077781.9 10 July 2002 (10.07.2002) EP
- (71) Applicant (for all designated States except US): CORUS TECHNOLOGY BV [NL/NL]; P.O. Box 10000, NL-1970 CA IJmuiden (NL).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): DENYS, Mark, Bernard [NL/NL]; Gaaspstraat 44-1, NL-1079 VE Amsterdam (NL). MEIJER, Hendrikus, Koenraad, Albertus [NL/NL]; De Waterdief 149, NL-1911 JR Uitgeest (NL).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Published:
— without international search report and to be republished upon receipt of that report

[Continued on next page]

(54) Title: METALLURGICAL VESSEL



(57) Abstract: Metallurgical vessel for iron and steel making comprising a bottom portion, a sidewall and a lance arrangement of at least two lances for supplying oxygen containing gas to the interior of the vessel in operation wherein each lance comprises an end portion for emitting oxygen containing gas characterised in that the lance arrangement is configured so as to achieve in operation a substantially downwardly directed flow of post-combusted gases at the side wall of the vessel and a substantially upwardly directed flow of post-combusted gases in the center of the vessel.

WO 2004/007777 A2